

PCOP Series Sprayers	PCOP-50-12V3-HR	PCOP-50-12V3-EHR	PCOP-50-WL25-2.5PP-HR	PCOP-50-WL45-5.5PP-EHR
Frame	Steel Powder Coated White	Steel Powder Coated White	Steel Powder Coated White	Steel Powder Coated White
Reel Mount	Steel Powder Coated White	Steel Powder Coated White	Steel Powder Coated White	Steel Powder Coated White
Tank	50 U.S. Gallons Poly	50 U.S. Gallons Poly	50 U.S. Gallons Poly	50 U.S. Gallons Poly
Pump(s)	3 Shurflo 12 Volt Diaphragm - 1 each 3.0 GPM/45 PSI for Agitation, 2 each 1.2 GPM/100 PSI for Spraying	3 Shurflo 12 Volt Diaphragm - 1 each 3.0 GPM/45 PSI for Agitation, 2 each 1.2 GPM/100 PSI for Spraying	Wuli WL25BC Plunger Pump - 4.75 gpm/710 psi	Wuli WL45BC Plunger Pump - 8.99 gpm/710 psi
Pump Drive	12 Volt DC Motor (3)	12 Volt DC Motor (3)	2.5 HP Power Pro Gas Engine	5.5 HP Power Pro Gas Engine
Hose Reel	Coxreels Brand 1125 Series Medium Manual Rewind	Coxreels Brand 1125 Series Medium 12 Volt Rewind	Coxreels Brand 1125 Series Medium Manual Rewind	Coxreels Brand 1125 Series Medium 12 Volt Rewind
Agitation	Single Power Jet	Single Power Jet	Single Bypass Jet	Single Bypass Jet
Plumbing	Standard 300 psi, Comes with brass & poly fittings	Standard 300 psi, Comes with brass & poly fittings	Standard 300 psi, Comes with brass & poly fittings	Standard 300 psi, Comes with brass & poly fittings
Filter	Yes - Suction	Yes - Suction	Yes - Suction	Yes - Suction
Gauge	Yes – Liquid Filled	Yes – Liquid Filled	Yes – Liquid Filled	Yes – Liquid Filled
Hose	300' of 3/8" PVC Spray Hose rated up to 600 psi	300' of 3/8" PVC Spray Hose rated up to 600 psi	300' of 3/8" PVC Spray Hose rated up to 600 psi	300' of 3/8" PVC Spray Hose rated up to 600 psi
Spray Gun	S-10/GES rated to 800 psi	S-10/GES rated to 800 psi	S-10/GES rated to 800 psi	S-10/GES rated to 800 psi
Wire Harness	Yes	Yes	No	Yes
Air Gap Fill	Included	Included	Included	Included
Lid Lock	Included	Included	Included	Included
Dry Weight (Approximate)	300 lbs.	310 lbs.	326 lbs.	365 lbs.
Width	37"	37"	37"	37"
Length	40"	40"	40"	40"
Height	24" to top of tank / 40" to top of reel	24" to top of tank / 40" to top of reel	25" to top of tank / 40" to top of reel	25" to top of tank / 40" to top of reel